

BV	événement le plus pénalisant	Débits de pointe de référence			Débits de pointe modélisation					
		30 ans	50 ans	100 ans	30 ans		50 ans		100 ans	
		m³/s	m³/s	m³/s	m³/s	Différence	m³/s	Différence	m³/s	Différence
BR 1	P 1.5hp15	5.1	6.1	7.0	5.1	0.0%	6.1	0.0%	7.0	0.0%
BR2	P 1.5hp15	3.0	3.6	4.1	3.0	0.0%	3.6	0.0%	4.1	0.0%
BR3	P 1.5hp15	1.2	1.4	1.6	1.2	0.0%	1.4	0.0%	1.6	0.0%
FER1	P 0.5hp10	0.2	0.3	0.3	0.2	-15.1%	0.2	-16.0%	0.2	-13.1%
FER2	P 0.5hp10	0.7	0.8	0.8	0.6	-18.2%	0.6	-20.2%	0.7	-16.8%
FER3	P 0.5hp10	1.3	1.4	1.4	1.1	-15.2%	1.2	-16.3%	1.2	-13.3%
FER4	P 1.5hp15	1.3	1.5	1.7	1.3	0.0%	1.5	0.0%	1.7	0.0%
FER5	P 1.5hp15	1.4	1.6	1.8	1.4	0.0%	1.6	0.0%	1.8	0.0%
RD1	P 0.5hp10	1.0	1.1	1.1	0.8	-20.8%	0.9	-21.8%	0.9	-18.2%
RD2	P 0.5hp10	0.3	0.4	0.4	0.3	-20.6%	0.3	-21.9%	0.3	-18.2%
RD3	P 0.5hp10	0.3	0.4	0.3	0.3	-20.9%	0.3	-21.9%	0.3	-18.4%
RD4	P 0.5hp10	0.7	0.8	0.8	0.6	-20.8%	0.6	-21.8%	0.6	-18.3%
RD5	P 0.5hp10	0.6	0.7	0.6	0.5	-20.7%	0.5	-21.8%	0.5	-18.2%
STE1	P 0.5hp10	1.3	1.4	1.4	1.0	-17.2%	1.1	-18.5%	1.2	-15.3%
STE2	P 0.5hp10	0.8	0.9	0.9	0.7	-15.1%	0.7	-16.2%	0.8	-13.2%
STE3	P 0.5hp10	0.5	0.6	0.6	0.4	-15.2%	0.5	-16.3%	0.5	-13.3%
STE4	P 0.5hp10	0.3	0.3	0.3	0.3	-14.0%	0.3	-15.6%	0.3	-12.5%
STE5	P 0.5hp10	0.3	0.3	0.3	0.2	-13.9%	0.2	-15.6%	0.3	-12.7%
STE6	P 0.5hp10	0.5	0.6	0.6	0.4	-19.3%	0.5	-21.5%	0.5	-18.2%
STE7	P 0.5hp10	0.2	0.2	0.2	0.1	-20.3%	0.2	-21.9%	0.2	-18.3%
STE8	P 0.5hp10	0.2	0.3	0.3	0.2	-15.3%	0.2	-16.0%	0.2	-13.4%
STE9-1	P 0.5hp10	0.2	0.2	0.2	0.2	-19.5%	0.2	-21.5%	0.2	-17.9%
STE9-2	P 0.5hp10	0.2	0.2	0.2	0.2	-19.5%	0.2	-21.5%	0.2	-17.9%
RAY1	P 0.5hp10	0.6	0.6	0.6	0.5	-17.2%	0.5	-18.6%	0.5	-15.5%
RAY2	P 0.5hp10	0.6	0.6	0.6	0.5	-13.9%	0.5	-15.6%	0.6	-12.5%
RAY3	P 0.5hp10	0.5	0.6	0.6	0.4	-18.1%	0.5	-20.1%	0.5	-16.7%
RAY4	P 1.5hp15	1.1	1.3	1.5	1.1	0.0%	1.3	0.0%	1.5	0.0%
RAY5	P 0.5hp10	1.0	1.1	1.2	0.9	-12.2%	1.0	-13.3%	1.0	-10.7%
RAY6	P 0.5hp10	0.4	0.5	0.5	0.4	-19.2%	0.4	-21.5%	0.4	-18.2%
RAY7	P 0.5hp10	0.2	0.2	0.2	0.2	-16.9%	0.2	-18.4%	0.2	-15.1%
RAY8	P 0.5hp10	1.2	1.3	1.3	1.0	-16.7%	1.1	-18.6%	1.1	-15.4%
RAY9	P 0.5hp10	1.2	1.3	1.4	1.0	-14.0%	1.1	-15.4%	1.2	-12.6%

BV	événement le plus pénalisant	Débits de pointe de référence			Débits de pointe modélisation					
		30 ans	50 ans	100 ans	30 ans		50 ans		100 ans	
		m³/s	m³/s	m³/s	m³/s	Différence	m³/s	Différence	m³/s	Différence
RAY10R	P 1.5hp15	6.1	7.3	8.5	6.1	0.0%	7.3	0.0%	8.5	0.0%
RAY10U	P 0.5hp10	2.2	2.5	2.5	1.9	-15.2%	2.1	-16.2%	2.1	-13.3%
RAY11	P 0.5hp10	0.6	0.7	0.7	0.5	-18.2%	0.5	-20.1%	0.5	-16.7%
RAY12	P 2hp30	11.2	13.3	15.9	10.8	-4.2%	12.8	-4.2%	15.2	-4.4%
CTR1	P 0.5hp10	0.1	0.1	0.1	0.1	-15.8%	0.1	-17.6%	0.1	-14.2%
CTR2	P 0.5hp10	0.9	1.0	1.0	0.8	-18.4%	0.8	-19.5%	0.9	-16.1%
CTR3	P 0.5hp10	2.1	2.3	2.3	1.7	-19.4%	1.9	-20.6%	1.9	-17.2%
CTR4	P 0.5hp10	1.0	1.1	1.1	0.8	-19.4%	0.9	-20.6%	0.9	-17.2%
CTR5	P 0.5hp10	1.4	1.5	1.5	1.2	-15.5%	1.3	-16.5%	1.3	-13.4%
CTR6	P 0.5hp10	1.6	1.7	1.8	1.4	-11.9%	1.5	-12.9%	1.6	-10.3%
CTR7	P 0.5hp10	1.0	1.1	1.1	0.9	-11.7%	0.9	-12.7%	1.0	-10.2%
CTR8	P 0.5hp10	0.3	0.4	0.4	0.3	-20.6%	0.3	-21.9%	0.3	-18.2%
CTR9	P 0.5hp10	0.4	0.5	0.5	0.3	-18.4%	0.4	-19.3%	0.4	-16.1%
CTR10	P 0.5hp10	1.3	1.4	1.4	1.1	-15.2%	1.2	-16.3%	1.2	-13.3%
CTR11	P 0.5hp10	0.8	0.9	0.9	0.7	-12.9%	0.8	-14.2%	0.8	-11.4%
CTR12	P 0.5hp10	2.4	2.7	2.7	2.0	-18.1%	2.2	-20.0%	2.3	-16.7%
CTR13	P 0.5hp10	2.9	3.3	3.3	2.6	-12.2%	2.8	-13.3%	3.0	-10.7%
CTR14	P 0.5hp10	0.5	0.6	0.6	0.4	-20.7%	0.4	-21.8%	0.5	-18.3%
GALI	P 2hp30	5.4	6.4	7.6	5.2	-3.8%	6.1	-3.8%	7.3	-3.9%
PILE EST 1	P 0.5hp10	4.4	4.9	4.9	3.8	-13.5%	4.1	-15.2%	4.3	-12.4%
PILE EST 2	P 0.5hp10	2.0	2.3	2.3	1.8	-11.9%	2.0	-12.9%	2.1	-10.2%
PILE OUEST 1	P 0.5hp10	2.8	3.1	3.1	2.4	-13.5%	2.6	-15.2%	2.7	-12.4%
PILE OUEST 2	P 0.5hp10	4.9	5.5	5.6	4.6	-7.3%	5.0	-8.2%	5.2	-6.2%
PILE AMONT	P 2hp30	5.4	6.4	7.6	5.2	-3.8%	6.1	-3.8%	7.3	-3.9%
NO1	P 2hp30	1.7	2.0	2.4	1.7	-2.0%	2.0	-2.1%	2.3	-2.1%
NO2	P 2hp30	2.1	2.5	3.0	2.1	-2.1%	2.5	-2.1%	2.9	-2.0%
NO3	P 2hp30	1.2	1.5	1.7	1.2	-1.9%	1.4	-2.0%	1.7	-2.0%